

With Elvita, you make room for all the things you appreciate. You get carefully selected products with smart solutions for a good price, designed to make life easy. Products for the entire household, making room for everyday life.









Adjustable fan Carbon filter speeds

(optional)

LED lamps

Easy to clean

CSF3600X Wall-mounted cooker hood

- 60 cm width
- 3 fan speeds
- Carbon filter or flue installation
- Low noise level (55-61 dB)
- Easy to clean

A classic cooker hood

This wall-mounted cooker hood is efficient yet has a low noise level. The classic look is suitable for any household. It has 3 fan speeds and built-in LED lamps, making the cooking easy.

Efficient performance at different fan speeds

The cooker hood lets you select a fan speed that suits your needs. This is a true friend in the kitchen, keeping the cooking environment fresh and grease-free.

Option to use with carbon filter

This cooker hood can be installed with an existing flue outlet. but also has the option to use a carbon filter. The carbon filter removes any impurities and odours from the air when it is recycled into the kitchen. Both installation options gives you a cooker hood with excellent performance.

Low-energy lamps

The built-in LED lamps gives effective lighting at a fraction of the energy spent compared to regular light bulbs, the life span is also remarkably longer.

Easy to clean filter

The removable aluminium grease filter are easy to clean. Handwash the filter or let the dishwasher do the dirty work. With little to no maintenance, this cooker hood is always exceeding expectations. Enjoy a fume-free and hassle-free cooking experience.



Product properties


Colour	Stainless steel
Installation	Wall-mounted
Type of control	Buttons
Filter type	Aluminium, carbon
LED lamps	2
Levels of speed	3
Backdraft damper	Yes


Technical specifications

iooninoan opoonioanionio	
Net weight	6.6 kg
Height, adjustable	572-902 mm
Width	600 mm
Depth	450 mm
Minimum height above electric range	650 mm
Minimum height above gas range	750 mm
Flue outlet, diameter	120 mm
Power supply	220-240 V, 50 Hz
Cord length, plug type	1.3 m, F-type
Rated power	131 W
Sound power level, min speed (LWA)	55 dB
Sound power level, max speed (LWA)	61 dB
Sound power level, boost (LWA)	-
Motor power	125 W
Maximum air flow	253 m³/h
Measured air flow rate at best efficiency point	160.1 m³/h
Energy efficiency class	D
Grease filtering efficiency class	С
Fluid dynamic efficiency	8.3
Nominal power of the lighting system	6 W
Model identifier	CSF3600X

For details about the energy efficency of the product, go to https://eprel.ec.europa.eu/. Use the model identifier to find information.

Dimensions





Energy label

